IEEE HOME | SEARCH IEEE | SHOP | WEB ACCOUNT | CONTACT IEEE

◆**IEEE**

Membership   Publications/Services   Standards   Conferences   Careers/Jobs

IEEE Xplore®
RELEASE 1.8

Welcome
United States Patent and Trademark Office

» Se.

Help   FAQ   Terms   IEEE Peer Review

Quick Links

Welcome to IEEE *Xplore®*

○ Home
○ What Can
     I Access?
○ Log-out

Tables of Contents

○ Journals
     & Magazines
○ Conference
     Proceedings
○ Standards

Search

○ By Author
○ Basic
○ Advanced

Member Services

○ Join IEEE
○ Establish IEEE
     Web Account

○ Access the
     IEEE Member
     Digital Library

IEEE Enterprise

○ Access the
     IEEE Enterprise
     File Cabinet

Your search matched **1** of **1064971** documents.
A maximum of **500** results are displayed, **15** to a page, sorted by **Relevance Descending** order.

Refine This Search:
You may refine your search by editing the current search expression or enteri new one in the text box.

cascade and current mirror and (biasing or bias) | Search |

☐ Check to search within this result set

Results Key:
JNL = Journal or Magazine   **CNF** = Conference   **STD** = Standard

1 **A 500-MHz monolithic CRT video driver using a linear array**
Kato, K.; Sase, T.; Sato, H.;
Custom Integrated Circuits Conference, 1990., Proceedings of the IEEE 1990
16 May 1990
Pages:25.4/1 - 25.4/4

[Abstract]   [PDF Full-Text (352 KB)]   **IEEE CNF**

🖳 Print Format

Home | Log-out | Journals | Conference Proceedings | Standards | Search by Author | Basic Search | Advanced Search | Join IEEE | Web Account |
New this week | OPAC Linking Information | Your Feedback | Technical Support | Email Alerting | No Robots Please | Release Notes | IEEE Online
Publications | Help | FAQ| Terms | Back to Top

- Drafts
  - ISNR:
  - Pending
- Active
  - L1: (780) cascade and current adj mirror and (biasing or bias) and control
  - L2: (163) 1 and RF
  - L3: (153) 2 and capacitor
- Failed
- Saved
- Favorites
- Tagged (0)
- UDC
- Queue
- Trash

Search | ... | Format | Query | Clear

DBs | USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB

Default operator | OR |

Plurals

Highlight all hits terms initially

2 and capacitor

BRS term | R4 Num | Image | Text | HTML

#	US		Document ID	Issue Date	Pages	Title	Current DR	Current XRef	Retrieval Class	Inventor	IS	C	P		A		
1	☐	☐	US 20040160286 A1	20040819	88	Applications for differential crystal oscillator	331/185			Ward, Christopher M. et al.	☑	☐	☐	☐	☐	☐	☐
2	☐	☐	US 20040085130 A1	20040506	4	Simple self-biased cascode amplifier circuit	330/288	330/311		Luo, Sifen	☑	☐	☐	☐	☐	☐	☐
3	☐	☐	US 20040077327 A1	20040422	94	Frequency modification circuitry for use in radio-frequency communication apparatus and associated methods	455/318	455/258; 455/319		Lim, Lysander et al.	☑	☐	☐	☐	☐	☐	☐
4	☐	☐	US 20030194978 A1	20031016	85	System and method for coarse/fine PLL adjustment	455/197.1	455/180.3; 455/315; 455/331		Vorenkamp, Pieter et al.	☑	☐	☐	☐	☐	☐	☐
5	☐	☐	US 20030189540 A1	20031009	33	Amplifier circuit and liquid-crystal display unit using the same	345/89			Itakura, Tetsuro et al.	☑	☐	☐	☐	☐	☐	☐
6	☐	☐	US 20030162521 A1	20030828	86	System and method for on-chip filter tuning	455/302	455/296		Vorenkamp, Pieter et al.	☑	☐	☐	☐	☐	☐	☐
7	☐	☐	US 20030155977 A1	20030821	11	Gain block with stable internal bias from low-voltage power supply	330/290			Johnson, Douglas M. et al.	☑	☐	☐	☐	☐	☐	☐
8	☐	☐	US 20030128071 A1	20030710	177	Variable transconductance variable gain amplifier utilizing a degenerated differential pair	330/254			Nguyen, Thinh Cat et al.	☑	☐	☐	☐	☐	☐	☐
9	☐	☐	US 20030107427 A1	20030612	85	Temperature compensation for internal inductor resistance	327/513			Vorenkamp, Pieter et al.	☑	☐	☐	☐	☐	☐	☐
10	☐	☐	US 20030097050 A1	20030522	11	Implantable signal amplifying circuit for electroneurographic recording	600/345			Baru Fassio, Marcelo Daniel	☑	☐	☐	☐	☐	☐	☐
11	☐	☐	US 20030067359 A1	20030410	61	Adaptive radio transceiver with a local oscillator	331/46			Darabi, Hooman et al.	☑	☐	☐	☐	☐	☐	☐

File | Details | HTML

Ready | NUM